



# Halogen non-reflector

## 6605 10W G4 6V 1CT/10X10F

Halogen non-reflector lamps offer high-quality light and are easy to install, replace and operate. All halogen non-reflector lamps incorporate a distortion-free quartz bulb and a precise positioning of the mounted filament. These ensure optimal beam performance and consistent, high light output. A wide range of wattages is available for a broad variety of applications, including projection systems. In addition you get all the proven advantages of halogen technology such as a full spectrum and a color rendering index (CRI) of 100 – the same as natural light and the best that it can be. Halogen lamps also create a comfortable warm white light, and they maintain their lumen output, with almost no reduction, throughout their lifetime.


### Product data

| General Information                |                                   |
|------------------------------------|-----------------------------------|
| Cap-Base                           | G4 [ G4]                          |
| Philips Code                       | 6605                              |
| ANSI Code                          | -                                 |
| LIF Code                           | M42                               |
| Operating Position                 | UNIVERSAL [ Any or Universal (U)] |
| Main Application                   | Projection                        |
| Life to 50% Failures (Nom)         | 2000 h                            |
| Light Technical                    |                                   |
| Luminous Flux (Nom)                | 150 lm                            |
| Correlated Color Temperature (Nom) | 2700 K                            |
| Color Rendering Index (Nom)        | 100                               |
| Operating and Electrical           |                                   |
| Power (Nom)                        | 10 W                              |
| Voltage (Nom)                      | 6 V                               |

| Mechanical and Housing          |                           |
|---------------------------------|---------------------------|
| Bulb Material                   | Quartz-UV Open            |
| Filament Dimensions WxH         | 2.8x0.5                   |
| Luminaire Design Requirements   |                           |
| Bulb Temperature (Max)          | 900 °C                    |
| Pinch Temperature (Max)         | 350 °C                    |
| Product Data                    |                           |
| Full product code               | 871150041009250           |
| Order product name              | 6605 10W G4 6V 1CT/10X10F |
| EAN/UPC - Product               | 8711500410092             |
| Order code                      | 923873910103              |
| Numerator - Quantity Per Pack   | 1                         |
| Numerator - Packs per outer box | 100                       |
| Material Nr. (12NC)             | 923873910103              |
| Net Weight (Piece)              | 0.001 kg                  |

# Halogen non-reflector

## Dimensional drawing



6605 10W G4 6V

| Product                   | D (max) | L (max)  | C (max) |
|---------------------------|---------|----------|---------|
| 6605 10W G4 6V 1CT/10X10F | 9.5 mm  | 19.75 mm | 31 mm   |

